
Release Notes for Meridian 1 X11 Release 25.40 Standard

This document provides updates and corrections to the Nortel Technical Publications (NTPs) for Meridian 1 X11 Release 25.40 Standard. Information is listed numerically by NTP number.

International ISDN Primary Rate Interface Feature description and administration (553-2901-301)

Refer to page 1627.

The Trunk Optimization (Before Answer) chapter should include the following new paragraph on call forwarding features.

Call Forward

If the OPT prompt in Overlay 15 is set to Call Forward Forwarding (CFF), the forwarding set's Class of Service is used to determine access to services or features when a call is forwarded. With Trunk Optimization (Before Answer), however, the originating set can restrict an optimized call to the forwarding set's DN, even though the forwarding set's Class of Service would have allowed the call to be completed.

Software Input/Output Guide (553-3001-311)

LD 57: Flexible Feature Codes

Refer to page 818.

The following two prompts (in bold type) have been corrected:

Prompt	Response	Comment
USTA	xxxx	User Status code
VTLF	xxxx	Virtual Terminal Logoff
VTLN	xxxx	Virtual Terminal Logon

Software Input/Output Guide (553-3001-411)

SCH: Service Change

Refer to page 970.

The following system message should include ACD.

SCH3127 Invalid AST key type. Only ACD, MCR, MCN, SCR and SCn keys are supported.

Software Input/Output Guide (553-3001-511)

LD 135: Core Common Equipment Diagnostic

LD 135 should include the following two commands:

- For SBFS x, refer to page 473.
- For STAT IPL cab, refer to page 477.

Command	Description
SBFS x	Force Media Gateway to Slave mode. Where x is: <ul style="list-style-type: none">• 1, 2, 3, or 4, Media Gateway
STAT IPL cab	Get the IP link status between CSE 1000 and Media Gateway